

# PRO-GYP

INTERIOR FINISHING PRODUCTS

## Submittal PRIME-COAT DRYWALL PRIMER

### PRIME-COAT DRYWALL PRIMER

- **PRIME-COAT is a ready to use drywall primer that is used between the final finishing coat of compound and the application of texture. Using this product will reduce texture variations on “orange peel” applications and promote consistent drying times for “knockdown” applications.**
- **Low VOC “Environmentally Friendly”**
- **Ready to use**
- **Fast dry time**
- **PVA**

#### APPLICATION

Recommended application of **PRIME-COAT** is by roller or airless spray. Airless spray is the preferred method of application and produces excellent results.

#### JOB CONDITIONS

A minimum temperature of 55° F (12.7° C) to be maintained 48 hours prior through application and until dry and stable.

#### MIXING

Mix by stirring. Power mixing is not recommended.

#### EQUIPMENT

Airless application (1.0 GPM) is recommended. Tip size of .019” to .031”. Air pressure range 2600 to 3200 psi.

#### COVERAGE

Approximately 200 sq ft per gallon. Actual coverage may vary depending on drywall surface, spraying techniques, coating uniformity and thickness.

#### DRYING TIME

Touch dry in approximately 20-40 min under normal drying conditions. Drying times may be altered with changes in ambient temps, excessive humidity.

#### CLEAN-UP

**PRIME-COAT** is water-soluble: clean up with water.

Submittal / Approval	
Signature	Stamp