

# **MATERIAL SAFETY DATA SHEET**

MSDS Name: PRO-GYP LEVEL 5

MSDS Number: PF4509-02

Version Number 0009

MSDS Date: 03/10/09

Page Number: 1 of 5

---

## **SECTION I - PRODUCT AND COMPANY INFORMATION**

Product Name: PRO-GYP LEVEL 5

CAS Number MIXTURE

Hazard Rating: Health: 1 Fire: 1 Reactivity: 0 PPI: E

EPA Registration NA

Company Identification: Professional Gypsum

1333 NW 32<sup>nd</sup> Ave

Camas, Wa 98607

Contact: CUSTOMER SERVICE

Telephone/Fax: 714 453 9025 / 714 453 9082

Emergency Phone (24 Hour): INFOTRAC

(800) 535-5053

Preparer PRO-GYP

Product Class WATERBASE PAINT

Trade Name PRO-GYP LEVEL 5

Product Code PGL5

## **SECTION II - INGREDIENT AND HAZARD INFORMATION**

Hazardous Ingredients

CAS Number % TSCA Health Fire React PP

(No hazardous ingredients known at this time.)

## **SECTION III - HAZARDS IDENTIFICATION**

PRIMARY ROUTES OF ENTRY:

Ingestion and/or inhalation.

CARCINOGENICITY:

This product does not contain any substance(s) listed as a carcinogen by NTP, IARC, or OSHA.

ACUTE (SHORT TERM) FOR PRODUCT:

EYES: Causes irritation.

SKIN: May cause skin irritation upon prolonged or repeated contact.

BREATHING: Causes slight irritation to nose and throat.

SWALLOWING: Ingestion may cause nausea, vomiting, diarrhea.

CHRONIC (LONG TERM) FOR PRODUCT OR COMPONENTS:

Prolonged or repeated breathing of sprays, mists, or dusts in excess of the suggested TLV may cause nasal and respiratory irritations.

PERMISSIBLE EXPOSURE LEVEL FOR PRODUCT:

No Threshold Limit Value (TLV) has been established for the product. Current Adopted Values listed by ACGIH suggests a TLV of 10 mg/m<sup>3</sup> as Inhalable Particulates Not Otherwise Classified for

sprays, mists or dust particulates generated during application or handling exposures.

---

# **MATERIAL SAFETY DATA SHEET**

MSDS Name: PRO-GYP LEVEL 5

MSDS Number: PF4509-02

Version Number 0009

MSDS Date: 03/10/09

Page Number: 2 of 5

---

## **SECTION IV - FIRST AID MEASURES**

**IF IN EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. If irritation continues, see a physician.

**IF ON SKIN:** Flush skin with water.

**IF SWALLOWED:** Induce vomiting. Call a physician immediately. Give large amounts of water or milk.

Never give anything by mouth to an unconscious or convulsing person.

**IF BREATHED:** Remove person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth.

If breathing is difficult, give oxygen. Call a physician.

## **SECTION V - FIRE-FIGHTING MEASURES**

Flammability Class III B

Flash Range: >200F

Explosive Range: Not Applicable

**EXTINGUISHING MEDIA:**

Extinguishing media: Product is non-combustible.

**SPECIAL FIREFIGHTING PROCEDURES:**

Use self-contained breathing apparatus with full face piece.

**UNUSUAL FIRE & EXPLOSION HAZARDS:**

None.

## **SECTION VI - ACCIDENTAL RELEASE MEASURES**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

**SMALL SPILLS:** Contain spill immediately. Use inert material to absorb spilled material. Place absorbed spill into secure container for removal.

**LARGE SPILLS:** Use caution; spilled material may be extremely slippery. Contain spill immediately and prevent from entering the sewer system. Use an inert material to absorb spilled product.

**NOTE:** Rinsing this material down a sanitary sewer system can cause negative impact on monitoring systems. Contact local sewer authorities before attempting any discharges.

## **SECTION VII - HANDLING AND STORAGE**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:**

**PROTECT FROM FREEZING.** Store product between 40 deg. F. and 120 deg. F. Frozen product may be irreversibly damaged. Product should be kept out of direct sunlight at all times. Keep container closed when not using.

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: PRO-GYP LEVEL 5

MSDS Number: PF4509-02

Version Number 0009

MSDS Date: 03/10/09

Page Number: 3 of 5

---

## SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

ACGIH TLV ACGIH TLV-C ACGIH STEL OSHA STEL OSHA PEL

RESPIRATORY PROTECTION:

Use an approved MSHA or NIOSH respirator for nuisance mists, dusts, or sprays.

VENTILATION:

Use adequate ventilation to keep airborne concentrations below the exposure standard listed in Section II and/or Section V.

PROTECTIVE GLOVES:

None normally required. Use is advisable.

EYE PROTECTION:

Wear approved splashproof chemical goggles. In a controlled environment where eye contact is minimal, Safety glasses with side shields may be sufficient protection.

OTHER PROTECTIVE EQUIPMENT:

Avoid contact with clothing, dried product may be irremovable.

## SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Form: LIQUID

Appearance/Color: WHITE

Odor: MILD

Solubility (in water): DISPERSIBLE

pH Value: 8.5 - 10.0

Boiling Range: (WATER) 212.F (100.C)

Vapor Pressure (mmHg): (WATER) 17.@ 68.F (20.C)

Melting Point: Not Available

Evaporation Rate: Unavailable

Vapor Density: Non Volatile

Partition Coefficient Not Available

% Volatile Volume INCLUDING WATER 69.2%

Specific Gravity: 1.4462

VOC SEE SECTION XVI

Molecular Weight: MIXTURE

## SECTION X - STABILITY AND REACTIVITY

Stability: This product is stable

Hazardous Polymerization: Hazardous polymerization will not occur

INCOMPATABILITY:

None

---

# **MATERIAL SAFETY DATA SHEET**

MSDS Name: PRO-GYP LEVEL 5

MSDS Number: PF4509-02

Version Number 0009

MSDS Date: 03/10/09

Page Number: 4 of 5

---

## **CONDITIONS TO AVOID:**

Acids, strong oxidizing agents.

## **HAZARDOUS DECOMPOSITION PRODUCTS**

Thermal decomposition or burning may produce carbon monoxide and/or carbon dioxide.

## **SECTION XI - TOXICOLOGICAL INFORMATION**

Lethal Dose Information (ppm)

### **ADDITIONAL TOXICOLOGICAL DATA FOR PRODUCT AND/OR INGREDIENTS:**

None known for product.

## **SECTION XII - ECOLOGICAL INFORMATION**

### **ECOLOGICAL INFORMATION FOR PRODUCT AND/OR INGREDIENTS:**

Aquatic toxicity not available.

## **SECTION XIII - DISPOSAL CONSIDERATIONS**

EPA Hazardous Waste Number NONE

### **WASTE DISPOSAL METHOD:**

Product must be disposed of properly under Federal/State regulations for industrial waste.

Disposal

to a landfill may be permitted pending compliance with 40 CFR 264.314 & 265.314. This product when spilled or disposed of is a non-hazardous waste as defined in RCRA regulations (40 CFR 261).

## **SECTION XIV - TRANSPORT INFORMATION**

UN Number NONE

UN Pack Group NA

UN Class NA

ICAO/IATA Class NONE

DOT Hazard Class NOT HAZARDOUS

### **CANADIAN TDG/WHMIS INFORMATION:**

PIN NUMBER: None

TDG: NA

TDG ACT CLASS: NA

WHMIS: D2B

OTHER NAMES: None

---

# **MATERIAL SAFETY DATA SHEET**

MSDS Name: PRO-GYP LEVEL 5

MSDS Number: PF4509-02

Version Number 0009

MSDS Date: 03/10/09

Page Number: 5 of 5

---

## **SECTION XV - REGULATORY INFORMATION**

EEC Classification Irritant

This product is not a listed hazardous substance.

## **SECTION XVI - OTHER INFORMATION**

ADDITIONAL PRECAUTIONS AND NOTES:

Do not dilute or mix with other materials unless advised by supplier.

VOC INFORMATION

A Certified Product Data Sheet (CPDS) as outlined under Title 40 Part 63, Subpart JJ, Section 63.801 Definitions, detailing VOC content, will be available upon request.

---

Last Page